



www.szjusun.cn

■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG#28~#16
- ◆ Applicable Wire: AWG#28~#16
- ◆ 额定电压: 600V DC,AC(rms)
- ◆ Rated voltage: 600V DC,AC(rms)
- ◆ 额定电流: 7A (AWG #16)
- ◆ Rated Current: 7A (AWG #16)
- ◆ 耐压值: 1500V AC/minute
- ◆ Withstand voltage: 1500V AC/min.
- ◆ 工作温度: -25°C ~ +85°C
- ◆ Working Temp : -25°C ~ +85°C
- ◆ 绝缘电阻: ≥1000 MΩ
- ◆ Insulation resistance: ≥1000 MΩ
- ◆ 接触电阻: ≤10mΩ
- ◆ Contact resistance: ≤10mΩ
- 材料 MATERIAL
- ◆ 绝缘体: 尼龙66, UL94-V2
- ◆ Insulator: Nylon66, UL94-V2
- ◆ 接触针: 黄铜
- ◆ Contact PIN: Brass

Poles	DIM.A	DIM.B
2	-	5.3
4	4.20	9.5
6	8.40	13.7
8	12.60	17.9
10	16.80	22.1
12	21.00	26.3
14	25.20	30.5
16	29.40	34.7
18	33.60	38.9
20	37.80	43.1
22	42.00	47.3
24	46.20	51.5

GENERAL TOLERANCE

XX	±0.40
X	±0.30
.X	±0.25
.XX	±0.15
X°	± 2°
.X°	± 1°

SCALE: 3:1

UNIT: mm

SIZE: A4

DRAWN:

CHECK:

APPROVE:

DATE:

DATE:

DATE:

DWG. NO. :

E:\DWG\Production

PARTS NO. :

5569-2xNAW

TITLE:

成品图

REV.

A

SHEET:

1/1



旭森实业(深圳)有限公司
JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD