



www.szjusun.cn

■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG#28~#16
  - ◆ Applicable Wire: AWG#28~#16
  - ◆ 额定电压: 600V DC,AC(rms)
  - ◆ Rated voltage: 600V DC,AC(rms)
  - ◆ 额定电流: 7A (AWG #16)
  - ◆ Rated Current: 7A (AWG #16)
  - ◆ 耐压值: 1500V AC/minute
  - ◆ Withstand voltage: 1500V AC/min.
  - ◆ 工作温度: -25°C ~ +85°C
  - ◆ Working Temp : -25°C ~ +85°C
  - ◆ 绝缘电阻: ≥1000 MΩ
  - ◆ Insulation resistance: ≥1000 MΩ
  - ◆ 接触电阻: ≤10mΩ
  - ◆ Contact resistance: ≤10mΩ
- 材料 MATERIAL
- ◆ 绝缘体: 尼龙66
  - ◆ Insulator: Nylon66, UL94-V2
  - ◆ 接触针: 黄铜
  - ◆ Contact PIN: Brass

Poles	DIM.A	DIM.B
2	-	5.3
4	4.20	9.5
6	8.40	13.7
8	12.60	17.9
10	16.80	22.1
12	21.00	26.3
14	25.20	30.5
16	29.40	34.7
18	33.60	38.9
20	37.80	43.1
22	42.00	47.3
24	46.20	51.5

恒泰实业(深圳)有限公司  
JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD

GENERAL TOLERANCE		SCALE: 3:1		DRAWN:		DATE:		DWG. NO. :		TITLE:		REV.	
XX. ±0.40		UNIT: mm	CHECK:	DATE:	E:\DWG\Production	PARTS NO. :		成品图		SHEET:		A	
X. ±0.30		SIZE: A4	APPROVE:	DATE:	5569-2xNA					1/1			
X. ±0.25													
.XX ±0.15													